

Canon

 **imageRUNNER**
LBP3480



desktop productivity
networked
managed document services ready

OFFICE SOLUTIONS





meap

At-a-Glance




imageRUNNER L B P 3 4 8 0

 **Compact Duplex Printing**

 **Up to 8.5" x 14"**

 **Up to 600 x 600 dpi**

 **Black and White**

Robust performance

- > Up to 35-ppm printing (Letter)
- > Standard UFR II, PCL 5e/6, and Adobe PostScript 3
- > Standard 768MB RAM
- > Fast warm-up time, 28 seconds or less
- > Fast first-print time, 7 seconds or less

Exceptional usability

- > User-friendly 5-line LCD display panel
- > Front-mount USB port for memory media print
- > Toner status display
- > Dedicated Job Cancel button
- > Available paper tray closing assist mechanism
- > Support for Canon imageWARE Enterprise Management Console

Outstanding paper handling

- > Up to 800-sheet maximum paper capacity
- > 50-sheet stack bypass tray
- > Auto-duplexing
- > Output Tray Full Detection

Remarkable connectivity and management

- > Consistent management tools with imageRUNNER ADVANCE MFP systems
- > Standard Ethernet and USB 2.0 Hi-Speed ports
- > Remote diagnostics and updates for maximum uptime
- > Device Link with imageRUNNER ADVANCE MFPs
- > Embedded MEAP brings MFP workflows to the desktop printer

Crisp black-and-white output. Fast operation, compact size, and user friendly for all.

Ready for Managed Document Services and Fleet Support

If you're looking for a device that extends the benefits of managed document services down to the desktop, then look no further. Managing imageRUNNER LBP printers and MFP devices is easy with imageWARE Enterprise Management Console software. Administrators can remotely monitor the status of an entire fleet of MFPs and printers across the network to help maintain uptime for users. The imageRUNNER LBP3480 model has been designed to fully integrate with imageWARE Remote, allowing your Canon Authorized Dealer to proactively and securely monitor usage, relay status, and even remotely update firmware, saving your business valuable time and resources.

Uncomplicated operation

Users will appreciate the clarity of the 5-line LCD display and intuitive control panel of the imageRUNNER LBP3480 model. The distinctive panel features on-screen navigation to facilitate device setup as well as animations to help guide operations. Replacing the all-in-one toner and drum cartridge is also simple—just press a single button to open the front access panel. Reloading paper is easier, too, with Canon's closing assist mechanism.* Easily print PDF, JPEG, TIFF, or XPS files without a computer via the standard front-mount USB port. And enjoy secure follow-me print release from Canon's powerful uniFLOW solution via an embedded MEAP integration—no release station required. A unique integration with imageRUNNER ADVANCE MFP devices lets you route in-bound faxes to your imageRUNNER LBP3480 printer, saving time and reducing fax lines.

Compact desktop performance

The Canon imageRUNNER LBP3480 printer is the ideal choice for small corporate workgroups and small offices. Leveraging Canon's patented RAPID Fusing System, this model produces ultra-crisp monochrome documents at up to 35 ppm (LTR). It also delivers quick first-print times and automatic duplexing, despite its compact size and low energy consumption—just 1W in Deep Sleep Mode. For larger print operations, an optional paper cassette allows for up to 800 total sheets. Canon's innovative paper-level sensor proactively prevents problems by detecting when the output tray is full, and then automatically resumes printing when the tray is emptied.

Flexible printing options

Support for UFR II, PCL5e/6, and Adobe PostScript 3 is standard on the imageRUNNER LBP3480 model, giving you the flexibility to choose how to produce your documents. UFR II is optimized to produce high-speed output by automatically sharing processing tasks between the desktop computer and the printer. Adobe PostScript 3 support delivers true rasterization of PS3 print data, particularly useful for design, publishing, education, and healthcare businesses. Canon's print driver architecture and intuitive layout are highly consistent for all driver types throughout the entire imageRUNNER and imageRUNNER ADVANCE line, simplifying use and ensuring a familiar user experience across different Canon systems. The imageRUNNER LBP3480 model is ready for business with support for multiple platforms including Citrix and SAP. The available Barcode Print Kit supports a wide variety of bar codes, while the optional SD Card adds support for Encrypted Secured Print and onboard document storage.



* Available on the optional Paper Feeder PF-44 cassette.

Product Specifications

Main Unit

Type	Desktop Laser Printer
Printing Method	Electrophoto Method (RAPID Fusing System)
Developing System	Contact Developing System
Standard PDL	UFR II, PCL 5e/6, Adobe Postscript® 3™
Power Supply	120-127V, 60Hz
Plug	NEMA 5-15P
Memory	Standard: 768MB RAM Maximum: 768MB RAM
CPU	ARMII-528MHz + ARM9-264MHz
Interface Connections	Shared 10/100/1000Base-TX (RJ-45)
Other Interface	USB Hi-Speed x1 USB (Host) x2
User Interface	LCD 22 Characters x 5 Line, 8 LED Indicators, 12 Operation Keys
Print Speed (BW)	35 ppm (Letter, 1-sided printing)

Warm-Up Time	28 Seconds or Less
First-Print Time	7 Seconds or Less
Resolution	Print: UFR II, PCL 5e/6, PS 3: 600 x 600 dpi 2400 Equivalent x 600 dpi Engine: 600 x 600 dpi Halftone: 256 Gradations (Continuous-Tone)
Print Drivers	UFR II, PCL 5e/6, Adobe PS3: Windows® (XP/Windows Vista*/Windows 7/Server 2003/Server 2008/Server 2008 R2/Small Business Server 2011), Windows Terminal Servers (Server 2008/Server 2008 R2), Small Business Server 2011, Microsoft Failover Cluster (Windows Server 2003/Server 2003 R2/Server 2008/Server 2008 R2), Citrix (Presentation Server 4.5, XenApp 5.0/6.0/6.5, XenDesktop 2.0/2.1/3.0/4.0/5.0/5.5), Macintosh (OS X 10.4.9 or later) (UFR II/PS only), VMware (vSphere 4/5), SAP (PCL/PS only)
Dimensions (H x W x D)	11-7/16" x 15-3/4" x 14-13/16" (289mm x 400mm x 376mm)
Installation Space (H x W x D)	16-3/4" x 15-3/4" x 32-7/8" (435mm x 500mm x 835mm) (when Multi-Purpose Tray is extended)

Weight	Approx. 25.6 lb. (11.6kg)*
Power Consumption (Approx., Average)	Operating: 550W Standby: 14W Deep Sleep Mode: 1W
Paper Sources	Standard: 250-sheet Paper Cassette (20 lb. Bond) 50-sheet Multi-Purpose Tray Optional: 500-sheet Paper Cassette Maximum: 800 Sheets
Paper Sizes	Cassettes: Legal, Letter, Executive, and 16K, Custom Sizes (Width: 4-1/8" to 8-1/2" Length: 5-7/8" to 14") Multi-Purpose Tray: Legal, Letter, Executive, and 16K, Custom Sizes (Width: 4-1/8" to 8-1/2" Length: 5-7/8" to 14") and Envelope Maximum Size: Legal (8-1/2" x 14")
Paper Weight	Cassettes: 16 lb. Bond to 32 lb. Bond (60 - 120g/m ²) Multi-Purpose Tray: 16 lb. Bond to 43 lb. Bond (60 - 163g/m ²)

Paper Handling	Paper Output: Face-down/Face-up Output Capacity: Approx. 150 Sheets/1 Sheet Duplexing: Standard Automatic Trayless Duplexing (Legal, Letter)
Toner	Black (Starter): 2,100 Standard Pages** Black: 6,400 Standard Pages**

Paper Feeder Unit PF-44 (Optional)

Paper Sizes:	Legal, Letter, Executive, Custom Sizes (Width: 4" to 8-1/2"; Length: 5-13/16" to 14")
Cassette Capacity:	500 Sheets (20 lb. Bond)
Dimensions (H x W x D)	6-1/2" x 14-1/2" x 17-3/8" (166mm x 390mm x 441mm)
Weight	Approx. 9 lb.(4.1kg)

Other Optional Accessories

- SD Card-B1 (8GB)
 - Barcode Printing Kit-F1
- * Excluding the CRG.
** Toner cartridge yield in accordance with ISO/IEC 19752.



1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that this product meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice.
©2013 Canon U.S.A., Inc. All rights reserved.

